

Arduino Training Kit



Kit Code :ES-ARDU

OVERVIEW

The EISAC Mobile Laboratory Training Kit is a high-performance development platform designed to eliminate the complexity of jumper wires and unstable breadboards. Engineered as a "System-on-Board," it provides a robust, protected, and organized environment for rapid firmware development and sensor integration. This kit is the ideal solution for engineers and students seeking to master the Arduino ecosystem, offering a seamless transition from basic coding to advanced industrial-style sensor networking.

TRAINING EXPERIMENTS

Environmental Monitoring: Building a digital weather station with OLED data logging

Smart Automation: Creating light-dependent systems using the integrated LDR sensor

Motion Electronics: Developing tilt-sensing alarms and step-counting algorithms

User Interface Design: Crafting menu systems and real-time graphs on the OLED display

Industrial Networking: Mastering I2C and UART serial communication between devices

SAFETY FEATURES

Connection Security: JST connectors prevent accidental polarity reversal and loose wiring.

Current Management: Integrated resistors to protect signaling LEDs and Buzzer circuits.

Stabilized Bus: Power distribution designed to prevent voltage drops during multi-sensor operation.

Circuit Clarity: High-quality silk-screen labeling for every pin to prevent wiring errors.

Master Control: Centralized power management for the controller and all peripheral sensors.

SYSTEM COMPONENTS

Control Unit	Integrated Socket for Arduino Nano (or compatible) controllers
Visual Interface	0.96" OLED Display Support for real-time graphics and data
Sensor Suite	Multi-Sensor Ecosystem (Environmental, Light, and Motion)
User Interaction	Tactile Push Button & Precision Rotary Potentiometer
Signaling Unit	Integrated Buzzer, Programmable LED, and Sound Output
Expansion Hub	Dedicated UART & I2C Bus for external module daisy-chaining

TECHNICAL SPECIFICATIONS

Processor Support	Fully compatible with Arduino Nano (Atmega328P) architecture
Environmental Sensing	Integrated Temperature, Humidity, and Barometric Pressure sensors.
Motion Analysis	On-board Acceleration Sensor for tilt and motion detection
Connectivity	Standardized JST connectors for secure, industrial-grade interfacing
Logic Levels	5V/3.3V compatible bus with dedicated I/O access (D2–D8 and A0–A3)
Signaling	Dual-mode feedback system utilizing both audible (Buzzer) and visual (OLED/LED) outputs

MECHANICAL SPECIFICATIONS

PCB Architecture: Industrial-grade, high-durability PCB with reinforced mounting points

Compact Design: Engineered as a "Mobile Lab" for high portability and space efficiency

Logical Partitioning: Components are intelligently grouped by function (Inputs, Outputs, Comms)

Interface Finish: Permanent, high-contrast labeling for all ports and component identifiers

Enclosure Ready: Dimensions optimized for standard laboratory desk use or custom housing

SOFTWARE & COMPATIBILITY

Programming IDE: Fully compatible with Arduino IDE, VS Code (PlatformIO), and MATLAB

Driver Support: Standard CH340/FTDI drivers for seamless PC connectivity

Library Support: Compatible with standard Adafruit/Arduino libraries for all on-board sensors



2026 EISAC Automation

This document and its contents are the exclusive property of EISAC Automation. Unauthorized reproduction, distribution, or modification of this material, in whole or in part, is strictly prohibited. Specifications are subject to change without notice.

Order Here



ES-ARDU